2/19/1

DIALOG(R) File 347: JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

07408307 \*\*Image available\*\*

WATER PUMP DEVICE

PUB. NO.: 2002-276816 [JP 2002276816 A] PUBLISHED: September 25, 2002 (20020925)

INVENTOR(s): MIYAKE NOBUHIKO

IWAKIRI SHIGERU

APPLICANT(s): NSK LTD

APPL. NO.: 2002-007801 [JP 20022007801]

Division of 2000-183947 [JP 2000183947]

FILED: January 30, 1990 (19900130)

INTL CLASS: F16J-015/32; F04D-029/04; F04D-029/12; F16C-019/04;

F16C-033/78

## ABSTRACT

PROBLEM TO BE SOLVED: To lengthen a life of a **bearing** by almost certainly preventing an intrusion of cooling water and steam into the **bearing** and simultaneously sealing grease in the **bearing**.

SOLUTION: A seal device has an outer ring side seal ring adjacent to a cavity relative to an impeller and fixed to an outer ring; and a shaft seal ring fixed to a shaft . The shaft side seal ring has a cylindrical part fitted/fixed to the shaft and an outer diameter direction part extending to an outer periphery direction therefrom. The outer ring side seal ring has a reinforcement ring; a main lip; a first sub- lip ; and a second sub- lip . The main lip extends from the reinforcement ring and is contacted with the shaft or an outer periphery surface of the cylindrical part of the **shaft** side seal fitted/fixed to the shaft . the first sub- lip extends from the reinforcement ring, is positioned at a rolling body side as compared with the main lip and is contacted with the shaft or the outer periphery surface of the cylindrical part of the **shaft** side seal fitted/fixed to the shaft . The second sub- lip extends from the reinforcement ring, is positioned at an opposite side of the firs sub- lip against the main lip and is contacted with the outer diameter direction part of the shaft side seal ring to form a closed space relative to the main lip .

COPYRIGHT: (C) 2002, JPO

C:\Program Files\Dialog\DialogLink\Graphics\5.bmp

3

